

Q8 Formula V Long Life 5W-30

Description

Synthetic SAE 5W-30 passenger car engine oil for normal and extended drain intervals.

Application

Specially formulated for Volkswagen passenger car gasoline and diesel engines meeting Euro 4 & Euro 5 with flexible drain intervals (WIV).

Backwards compatible with all engines (including R5 and V10 TDI engines) requiring VW 501.01, 502.00, 503.00, 503.01, 505.00, 505.01, 506.00 and diesel engines requiring 506.01*.

Recommended for ACEA C2 applications used by Peugeot Citroën for Euro 4 & 5 passenger car gasoline and diesel engines.

Specifications

- VW 504.00 level
- VW 507.00 level
- Backwards compatible with 501.01, 502.00, 503.00, 503.01, 505.00, 505.01, 506.00 and diesel engines requiring 506.01*.
- MB 229.51
- BMW Longlife-04
- ACEA C3
- ACEA C2 suitable for use

Benefits

- Lubricant designed for VW passenger car gasoline and diesel engines for Euro 4 & Euro 5 models.
- Backwards compatible with most VW gasoline engines and diesel engines with or without pump injectors.
- Extended drain interval capability compatible with flexible ODI systems .
- High oil film strength under all engine operating conditions.
- Excellent engine performance at all driving conditions .
- Outstanding protection against foam formation, rust and corrosion .

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Absolute Density, 15 °C	D 4052	kg/m ³	848
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.6
Kinematic Viscosity, 40 °C	D 445	mm ² /s	70.5
Viscosity Index	D 2270	-	159
Apparent Viscosity, -30 °C	D 5293	mPa.s	6117
Sulphated Ash	D 280	% mass	0.6
Pour Point	D 97	°C	-39
Flash Point	D 92	°C	209
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

